



Proton Pack Pro Decals - Plain
10-22-2011 valentino_42 Rev. 13



DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

F1
10A 115V

F1
10A 115V

F1
10A 115V

F1
10A 115V

F2
5A 115V

F2
5A 115V

F2
5A 115V

F2
5A 115V

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

FILLER PLUG & AIR VENT
ABOVE-20°F. USE OIL.
SPEC. MIL-H-5606
BELOW-20°F. USE OIL SPEC.
MIL-H-5606 MIXED WITH 26%
NAPHTHA SPEC TT-N-95
CAUTION CLOSE AIR VENT
WHEN NOT IN USE

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT



ACTIVATE





ACTIVATE

INTENSIFY

INTENSIFY

SLO-BLO

SLO-BLO





Proton Pack Pro Decals - Foil
10-22-2011 valentino_42 Rev. 13

Clippard
INSTRUMENT LABORATORY, Inc.
Cincinnati, Ohio 45239
Minimatic®
U.S. PAT. NO'S 3.766.935: 3.766.831 PAT'S PEND.

MADE IN U.S.A.

3 - Way Delay R331



Clippard
INSTRUMENT LABORATORY, Inc.
Cincinnati, Ohio 45239
Minimatic®
U.S. PAT. NO'S 3.766.935: 3.766.831 PAT'S PEND.

MADE IN U.S.A.

Pressure Reg. R701

MOTOR-SYNCHRONOUS (DM)

CONTINUOUS DUTY THERMAL PROTECTED
1/35 H.P., 1PH., 115 V.A.C., 50/60 HZ
1500/1800 R.P.M. .75/.65 AMPS
CAP. 5 MFD 370 VAC
INSULATION CLASS B
PART NO. 252193



WARNING
FOR-043 ANGLE GEARBOX ASSYS
USE ONLY HYDRAULIC PUMPS
THAT HAVE "O" RING TYPE
GREASE RETENTION SPLINES
(67WAF200 PUMP OR EQUIVALENT)
SS9013-1167

- WARNING -
FOR CONTINUED PROTECTION
AGAINST FIRE HAZARD, REPLACE
FUSES WITH SAME TYPE AND
RATING ONLY.

3AG 10A 250V PB
3AG 10A 32V MB
3AG 10A 32V MB
3AG 15A 32V MB

MOTOR-SYNCHRONOUS (DM)

CONTINUOUS DUTY THERMAL PROTECTED
1/35 H.P., 1PH., 115 V.A.C., 50/60 HZ
1500/1800 R.P.M. .75/.65 AMPS
CAP. 5 MFD 370 VAC
INSULATION CLASS B
PART NO. 252193

WARNING
FOR-043 ANGLE GEARBOX ASSYS
USE ONLY HYDRAULIC PUMPS
THAT HAVE "O" RING TYPE
GREASE RETENTION SPLINES
(67WAF200 PUMP OR EQUIVALENT)
SS9013-1167

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

DANGER
HIGH VOLTAGE 1KV
ELECTRIC SHOCK HAZARD
REMOVE POWER BEFORE
REPAIR OR ADJUSTMENT

CAUTION-HOT
ALLOW TO COOL
BEFORE REMOVAL
HANDLE CAREFULLY-
DELICATE LAMP FILAMENT